

# SPRING TESTER SW Series





# **Features**

- It can measure both compression and tension springs
- Product number registration can be registered up to 100th
- Printing results by built-in Printer
- Easy operate for condition setting and product number registration on touch panel screen
- Optional PC software available
- Spring rate, Free length, Solid hight, Pre-tension, Step operation(Up to 3 steps)

アイコーエンジニアリング、株式会社 AIKOH ENGINEERING CO., LTD.


# ■ Specifications

| Model                      | SW-1   | SW-5   | SW-10    | SW-50 | SW-100                   | SW-100T                                    | SW-200T | SW-500T                   |  |
|----------------------------|--|--------|----------|-------|--------------------------|--|---------|---------------------------|--|
| Capacity                   | 10N  | 50N    | 100N     | 500N  | 1000N                    | 1000N                                      | 2000N   | 5000N                     |  |
| Force resolution           | 0.0001N  | 0.001N | 0.001N   | 0.01N | 0.01N                    | 0.01N                                      | 0.1N    | 0.1N                      |  |
| Measuring range            | 0.5% to 100% F.S.( At the time of Force measurement or take Spring rate) |        |          |       |                          |  |         |                           |  |
| Force acuracy              | ±0.2% F.S.   |        |          |       |                          |  |         |                           |  |
| Unit of measurment         | kgf (N, lb, inch for lengh measurement)                                  |        |          |       |                          |  |         |                           |  |
| Test speed                 | 10 to 600 mm/min   |        |          |       |                          |  |         |                           |  |
| Max. measurable length     | 205mm 390mm  |        |          |       |                          |  | 600mm   |                           |  |
| Min.length reading         | 0.001mm  |        |          |       |                          |  |         |                           |  |
| Length accuracy            | $\pm$ 0.05mm (with in the range 150mm) $\pm$ 0.1mm (with in the range    |        |          |       |                          |  |         | 500mm)                    |  |
| Manual operation           | Select from these LOW, MID, HIGH,  |        |          |       |                          |  |         |                           |  |
| Compression plate diameter | Upper $\varphi$ 20Upper $\varphi$ 60Lower $\varphi$ 60Lower $\varphi$ 60 |        |          |       |                          | Upper $\varphi$ 150<br>Lower $\varphi$ 150 |         |                           |  |
| Hook for tensil test       | 1 stages   |        | 2 stages |       |                          | 1 stages                                   |         | Optional                  |  |
| Size                       | W460×D350×H541mm   |        |          |       | W460×<br>D350×<br>H741mm | W860×<br>D540×<br>H1372mm                  |         | W860×<br>D540×<br>H1350mm |  |
| Weight Approx.             | Approx. 45kg   |        |          |       | Approx. 70kg             | Approx. 190kg                              |         | Approx. 200kg             |  |
| Power supply               | AC100V to 240V   |        |          |       |                          |  |         | AC100V                    |  |

## Print function

Printing results by built-in Printer. It can Print [Date] resisterd [Model number] [Value] [OK or NG].

### Print sample



# Operation panel




### Measurement Screen

Set the Step operation, set the comparate value.



### **Test Condition**

Set the measurement condition. It can save as Item number.



### Item number resist

It can resist the Item number. It can set up to 100th.

# AIKOH ENGINEERING CO., LTD.

### http://www.aikoh.co.jp

TOKYO TANI BUILDING 4F 28-6, 1-Chome, Kameido, Koto-ku, Tokyo TEL (03)5858-8816 FAX (03)5858-8836

NAGOYA 210,2-Chome,Sakuta,Nagakute city,Aichi TEL (0561)64-2331 FAX (0561)64-2332 15-7,2-Chome,Hishie,Higashi-Osaka city,Osaka

OSAKA TEL (072)966-9011 FAX (072)966-9017

Overseas sales dept.

Osaka office 15-7, 2-chome Hishie Higashi-Osaka, Japan TEL +81-72-966-9011 FAX +81-72-966-9017